



HOLEMAKING

Drill Driven Punch Driver Knockout Set — Stainless Steel

- Punch up to a 2" conduit size hole in a maximum of 10 gauge stainless steel
- No hydraulic oil
- 1/2" to 2" punches designed to split the slug into two pieces for easy removal
- Punches are manufactured from tool steel for high strength and long life
- Recommended drill – (provided by end user) – 1/2" cordless drill with a minimum of 18 volts
- Fast, easy punching – no ratcheting
- Made in the USA



*Piecemaker™ SS
Punches are designed
to split the slug into two
pieces for easy removal
from die after punch
completion.*

**Current Tools™
Punch Driver
may be used with
Greenlee* Punches
and dies**



Model 162SS

Catalog Number	Description	Weight
163	Drill Driven Punch Driver	6 lbs.
162SS	1/2" – 2" Piecemaker™ SS Drill Driven Knockout Set	19 lbs.

**Greenlee is registered trademark of Greenlee/Textron.*



Current Tools
FOR THE PROFESSIONAL ELECTRICIAN

www.currenttools.com

P.O. Box 17026 • Greenville, SC 29606 • 864.244.1201 • fax 864.244.5860 • 800.230.5421



Drill Driven Punch Driver Knockout Sets — Stainless Steel

Item Number	Catalog Number	Description	163	162SS ½" to 2"
1	163	Punch Driver	1	1
2	163-14	Nut Driver		1
3	1574	¾"-7/16" X 4¼" SS Draw Stud		1
4	1575	¾" X 5½" SS Draw Stud		1
5	1553	Spacer – S		1
6	1505	Metal Case – 162SS		1
7	1536	½" SS Punch		1
8	1537	½" SS Die		1
9	1538	¾" SS Punch		1
10	1539	¾" SS Die		1
11	1542	1" SS Punch		1
12	1543	1" SS Die		1
13	1544	1¼" SS Punch		1
14	1545	1¼" SS Die		1
15	1546	1½" SS Punch		1
16	1547	1½" SS Die		1
17	1548	2" SS Punch		1
18	1549	2" SS Die		1



*PieceMaker™ SS
Punches are designed
to split the slug into two
pieces for easy removal
from die after punch
completion.*



162SS

