



## PULLING ACCESSORIES

### Pulling Grips — 00674 & 00675 Series

DOUBLE WEAVE – SINGLE EYE – SLACK GRIP – CLOSED MESH

These grips offer a Flexible Eye and Double Weave galvanized wire construction for those times when a side loaded pulling rope is easier. If the cable end is available, then the Closed Mesh is preferred.



Catalog Number	Size Range	Mesh Length	Approx. Breaking Strength	Weight
00674-010	0.38" to 0.74"	14"	2,500 lbs.	0.44 lb.
00674-020	0.75" to 1.12"	17"	3,000 lbs.	0.48 lb.
00674-030	1.13" to 1.49"	18"	5,000 lbs.	0.84 lb.
00674-040	1.50" to 1.99"	20"	10,000 lbs.	1.41 lbs.
00675-050	2.00" to 2.49"	21"	11,000 lbs.	2.56 lbs.
00675-065	2.50" to 2.99"	22"	12,000 lbs.	2.64 lbs.
00675-080	3.00" to 3.74"	23"	15,000 lbs.	2.95 lbs.
00675-095	3.75" to 4.24"	24"	15,000 lbs.	4.63 lbs.

### Pulling Grips — 00678 & 00679 Series

DOUBLE WEAVE – SINGLE EYE – SLACK GRIP – SPLIT MESH (Lace-Up)

These grips offer a Flexible Eye and Double Weave galvanized wire construction for those times when a side loaded pulling rope is easier. If the cable end is not available, then the Split Mesh is preferred.



Catalog Number	Size Range	Mesh Length	Approx. Breaking Strength	Weight
00678-010	0.38" to 0.74"	14"	4,100 lbs.	0.44 lb.
00678-020	0.75" to 1.12"	17"	4,970 lbs.	0.55 lb.
00678-030	1.13" to 1.49"	18"	8,150 lbs.	0.82 lb.
00678-040	1.50" to 1.99"	20"	12,100 lbs.	1.39 lbs.
00679-050	2.00" to 2.49"	21"	16,140 lbs.	1.92 lbs.
00679-065	2.50" to 2.99"	22"	16,140 lbs.	2.00 lbs.
00679-080	3.00" to 3.74"	23"	20,170 lbs.	2.20 lbs.
00679-095	3.75" to 4.24"	24"	23,400 lbs.	3.09 lbs.

*Always read Breaking Strength, safety and technical data information.*



**Current Tools**  
FOR THE PROFESSIONAL ELECTRICIAN

[www.currenttools.com](http://www.currenttools.com)

P.O. Box 17026 • Greenville, SC 29606 • 864.244.1201 • fax 864.244.5860 • 800.230.5421