



## Pulling Grips — 00680 Series

DOUBLE WEAVE – SINGLE EYE – SHOULDERS

These grips offer a FLEXible Eye with Shoulders and Double Weave galvanized wire construction. The shoulders offer added protection to the cable being pulled in as well as protecting the leading wire strands.



Catalog Number	Size Range	Mesh Length	Approx. Breaking Strength	Weight
00680-025	0.25" to 0.49"	18"	4,800 lbs.	0.4 lb.
00680-038	0.50" to 0.74"	24"	5,800 lbs.	0.4 lb.
00680-050	0.75" to 1.12"	24"	6,700 lbs.	0.5 lb.
00680-100	1.13" to 1.49"	24"	10,000 lbs.	0.6 lb.
00680-125	1.50" to 1.99"	24"	16,400 lbs.	1.3 lbs.
00680-200	2.00" to 2.49"	24"	18,500 lbs.	1.5 lbs.
00680-250	2.50" to 2.99"	36"	24,500 lbs.	2.5 lbs.
00680-300	3.00" to 3.74"	36"	24,500 lbs.	2.7 lbs.
00680-350	3.75" to 4.24"	42"	31,000 lbs.	4.2 lbs.
00680-400	4.25" to 4.99"	48"	31,000 lbs.	4.9 lbs.

## Pulling Grips — 00681 Series

TRIPLE WEAVE – SINGLE EYE – SHOULDERS

These grips offer a Flexible Eye with Shoulders and Triple Weave galvanized wire construction. The shoulders help to protect the leading edge of the cable and this type should be used for heavy duty applications.



Catalog Number	Size Range	Mesh Length	Approx. Breaking Strength	Weight
00681-006	0.25" to 0.49"	28"	6,500 lb.	0.5 lb.
00681-012	0.50" to 0.74"	33"	10,400 lb.	0.9 lb.
00681-019	0.75" to 0.99"	41"	16,000 lb.	1.8 lbs.
00681-025	1.00" to 1.24"	51"	25,400 lb.	3.1 lbs.
00681-032	1.25" to 1.49"	60"	31,700 lb.	4.0 lbs.
00681-038	1.50" to 1.99"	70"	32,000 lb.	4.5 lbs.
00681-048	2.00" to 2.49"	75"	44,600 lb.	4.7 lbs.

*Always read Breaking Strength, safety and technical data information.*

[www.currenttools.com](http://www.currenttools.com)

P.O. Box 17026 • Greenville, SC 29606 • 864.244.1201 • fax 864.244.5860 • 800.230.5421

**Current Tools**   
FOR THE PROFESSIONAL ELECTRICIAN