


## Can-Link Connector — 00520 Series

 The 00520 Connector is used to connect two items with lugs or wire loop fittings. A common use is to connect a wire mesh grip to the pulling wire. The connectors are manufactured from high strength Stainless Steel with hardened Clevis Pins. The two smaller sizes have slotted Clevis Pins while the larger ones have hexagon Clevis Pins.





Catalog Number	*Safe Working Load	A	В	С	D	E	Weight	
00520-010	2,500 lbs.	7/8"	3/8"	5/16"	2 1/8"		0.19 lbs.	UPC 811993023347
00520-020	5,000 lbs.	1 1/4"	17/32"	13/32"	2 7/8"		0.50 lbs.	UPC 811993023354
00520-027	9,000 lbs.	1 1/2"	19/32"	1/2"	3 3/8"		0.80 lbs.	UPC 811993023361
00520-035	15,000 lbs.	2"	25/32"	11/16"	4 9/16"		2.00 lbs.	UPC 811993023378


<sup>\*</sup>Safety Factor of 3:1

## Rope to Swivel Connector - 00522 Series

 This product is used to connect a swivel to pulling rope. The entire product, including sheave, is manufactured from stainless steel.

## **Line Swivel Selection**

Connect	or # Use with these Line Swivels
00522-	025: 00505-020 00505-025 00505-027
00522-	035: 00505-030 00505-035





Catalog Number	*Safe Working Load	Maximum Rope Diameter	Α	В	С	D	Е	Weight	
00522-025	7,000 lbs.	7/8"	2"	15/16"	11/16"	5 5/16"	1/2"	2.10 lbs.	UPC 811993023385
00522-035	15,000 lbs.	7/8"	2"	15/16"	11/16"	5 3/8"	21/32"	2.30 lbs.	UPC 811993023392
00522-040	30,000 lbs.	7/8"	2"	15/16"	11/16"	5 3/8"	21/32"	3.9 lbs.	UPC 811993026485

<sup>\*</sup>Safety Factor of 3:1