

HOLEMAKING

- Punch up to **2" holes** in a maximum of **10 gauge stainless steel**
- Punch **2 1/2" to 4"** with optional **Model #166SS Set** (see pages 56 and 57)
- **1/2" to 2" punches** designed to split the slug into two pieces for **easy removal**
- Punches are manufactured from tool steel for **high strength** and **long life**
- Recommended drill – (provided by end user **1/2" cordless drill with a minimum of 18 volts**)
- No hydraulic oil
- **Fast, easy** punching – no ratcheting
- **Made in the USA**



MODEL 162SS



Piecemaker™ Punches are designed to split the slug into two pieces for easy removal from die after punch completion



Scan Here For Manual

Catalog #	Description	Weight	UPC#
165	Drill Driven Punch Driver	6 lbs.	811993026539
162SS	1/2" – 2" Piecemaker™ Stainless Steel Drill Driven Knockout Set	19 lbs.	811993021077

HOLEMAKING

Item #	Catalog #	Description	165SS	162SS - 1/2-2	UPC #
1	165	Punch Driver	1	1	811993026539
2	163-14	Nut Driver	—	1	811993021084
3	1574	3/4" - 7/16" X 4 1/4" SS Draw Stud	—	1	811993021688
4	1575	3/4" X 5 1/4" SS Draw Stud	—	1	811993021695
5	1553	Spacer – S	—	1	811993020001
6	1505	Metal Case – 162SS	—	1	811993025303
7	1536	1/2" SS Punch	—	1	811993021435
8	1537	1/2" SS Die	—	1	811993021442
9	1538	3/4" SS Punch	—	1	811993021459
10	1539	3/4" SS Die	—	1	811993021466
11	1542	1" SS Punch	—	1	811993021497
12	1543	1" SS Die	—	1	811993021503
13	1544	1 1/4" SS Punch	—	1	811993021510
14	1545	1 1/4" SS Die	—	1	811993021527
15	1546	1 1/2" SS Punch	—	1	811993021534
16	1547	1 1/2" SS Die	—	1	811993021541
17	1548	2" SS Punch	—	1	811993021558
18	1549	2" SS Die	—	1	811993021565

162SS

