

CABLE PULLING

- Hinged upper drive to allow for **easy side loading**
- High grip tires can accommodate **no lube or regular cable**
- Dual drive motors for **maximum grip** on cables
- Cable separator guides cables to ensure **positive grip on tires**
- **Heavy duty** transport caster with quick release mechanism
- **Variable speed control**
- May be operated with **remote pendant** or **optional foot switch**
- **Self-lubricating** drive chains reduce maintenance
- Flat-free transport wheels
- **Made in the USA**



Can be used with
SIMPull® and
 other cables that
 do not require
 lubrication.


Optional Foot Switch

Features

- Hinged upper drive with gas spring assist for ease of cable loading from the side of the cable feeder
- Each tire independently driven for maximum pulling power
- Variable speed control
- Low voltage hand control pendant with a 8' long cable
- Ratcheting tension adjustment provides tension on the cable from 1/4" to 3 1/2" in diameter
- Removable cable separator
- Self-lubricating drive chains

Specifications

- Weight: 345 lbs.
- Dimensions: 26"W X 42"L X 43"H
- Power requirements: 115 VAC, 15 amps, 60 Hz
- Feeding speed: 0 ft./min to 36 ft./min.
- Cable capacity:
 Cable size — .25" to 3.5" dia. max.
 Total width of all cables — 6" max.
- Maximum pulling force:
 Single cable – Approximately 250 lbs.
 All cables – Approximately 1,000 lbs.
- Maximum reel capacity – 25,000 lbs.



Scan Here For
 Manual

Catalog #	Description	Weight	UPC#
99	Cable Feeder	345 lbs.	811993022210
99-122	Foot Switch (optional)	3 lbs.	811993022227

**** SIMPull® is a registered trademark of Southwire Company, LLC**